



Level (100:4006 Hz) = 95.66 dB SPL/watt (8 ohms, @1.00 meters)

DX12HE OPR.

MLSSA: Frequency Domain

MLSSA SPO 4.0D #960903-3057-3075 for Pro Dance Praha

Measured Data

QC Limits

Line	Parameter	Value	Units
1	RMSE-free	0.62	Ohms
2	Fs	65.22	Hz
3	Re	5.47	Ohms[dc]
4	Res	104.92	Ohms
5	Qms	7.14	
6	Qes	0.37	
7	Qts	0.35	
8	L1	0.76	mH
9	L2	1.61	mH
10	R2	5.29	Ohms
11	RMSE-load	0.41	Ohms
12	Vas(Sd)	55.43	liters
13	Mms	40.80	grams
14	Cms	146	$\mu\text{M}/\text{Newton}$
15	B1	15.68	Tesla-M
16	SPLref(Sd)	98.0	dB[Re]
17	Rub-index	0.00	

Method: Mass-loaded (50.00 grams)

Area (Sd): 520.00 sq cm

DCR mode: Measure (-0.29 ohms)

QC file: CLOSED

Analysis successful. Shift in Fs = -30.8% (-20% to -50% is recommended).

FANE DX 12 HE 8 ohm

MLSSA: Parameters